Armstrong



₩ FLOORING

Product overview 2014





RECOMMENDATION FOR HEALTHCARE



OFFICES, STAFF ROOMS					
mpact sound absorption	● ● Acoustic	Acoustic		••	•)))
Castor chair suitability	••	••	•	••	
Durability	••	••	•	••	
LABORATORY					
Resistance to chemicals	● ● PUR	● ● PUR	• PUR		/ >
Easy cleaning	● ● PUR	● ● PUR	● PUR		
Castor chair suitability	● ● PUR	● ● PUR	● ● PUR		
f necessary conductivity	LCH	● ● Conductive			
If necessary decontamination	● PUR	● ● PUR			₩
EXAMINATION ROOMS					
Easy cleaning	● ● PUR	● ● PUR	● ● PUR		
3acteriostatic	••				X
Freading warmth	••				
Castor chair suitability	••	••			6
T ROOMS					
Conductivity	● ● LCH	● ● Conductive		Conductive	Ź
CORRIDORS, STAIRS					
Durability	••	••	● PUR		
mpact sound absorption	● ● Acoustic	● ● Acoustic		••	•)))
Easy cleaning	● ● PUR	● ● PUR	••	•	
ENTRANCE HALL					
Smart appearance	•	•	••	•	
Aesthetics, atmosphere	•	•	••	•	
Durability	••	••	••	•	
Easy cleaning	● ● PUR	● ● PUR	● ● PUR		
Slip resistance R 9	••	••	••		

[●] Recommended ● ● Highly recommended

^{*}Special verification or certificate for this segment additionally to the common technical product features.






AND NEGOTIEMENTO					
LOUNGE					
Aesthetics, atmosphere	•	•	••		
Durability	••	••	••		
Easy cleaning	• PUR	● PUR	••		
OPERATING THEATRE					
Conductivity		● ● Conductive			<u> </u>
Hygiene		● ● Conductive			
Easy cleaning		● ● Conductive			
Disinfectant resistance		● ● Conductive			X
Indentation resistance		● ● Conductive			
Durability		● ● Conductive			
SURGERY					
Conductivity		● ● Conductive/ESD			<u> </u>
Hygiene		● ● Conductive/ESD			<u>△</u> .
Disinfectant resistance		● ● Conductive/ESD			X
Indentation resistance		● ● Conductive/ESD			
Durability		● ● Conductive/ESD			
DIALYSIS					
Hygiene	● ● PUR	● ● PUR	● PUR		
Easy cleaning	● ● PUR	● ● PUR	● PUR		
Durability	● ● PUR	● ● PUR	● PUR		
Disinfectant resistance	● ● PUR	● ● PUR	● PUR		X
Conductivity	● ● LCH	● ● Conductive			

RECOMMENDATION FOR HEALTHCARE SPORTS AREA AND REQUIREMENTS

THERAP, GYM	į.					
Resilience	• Acoustic				••	
Force disassembly					••	
Slip resistance R 9	••	•				Ę,
Impact sound absorption	● ● Acoustic	● ● Acoustic		•	Linogym II	>)))
TREATMENT ROOMS						
Aesthetics, atmosphere	•	•	••			
Treading warmth	••	•				
Individuality			••			
Cosy atmosphere	••	•	••			
Hygiene	● ● PUR	● ● PUR	• PUR			
Bacteriostatic	•					X
X-RAY ROOM						
Easy cleaning	● ● PUR	● ● PUR	● PUR			
Treading warmth	••					
Durability	● ● PUR	● ● PUR	● ● PUR			
Castor chair suitability	● ● PUR	● ● PUR	● ● PUR			
Conductivity	● ● LCH	● ● Conductive				
STORAGE ROOMS						
Durability	● ● Linodur	● ● Homogeneous				
Suitability for fork lifts	● ● Linodur	Homogeneous				
Indentation resistance	● ● Linodur	● ● Homogeneous				
Slip resistance R 9	● ● Linodur	● ● Homogeneous				F



RECOMMENDATION FOR EDUCATION



OFFICES						
Impact sound absorption	● ● Acoustic	• Acoustic		••)))
Castor chair suitability	••	••	•	••		
Durability	••	••	•	••		
Aesthetics	•	•	••	•		
CLASSROOMS				·		
Aesthetics, atmosphere	••	••	•	•		
Durability	••	••	•	••		
Slip resistance R 9	••	••	•			Ē
Impact sound absorption	• Acoustic	• Acoustic		••)))
Hygiene	••	•	•			Õ
Treading warmth	••			••		
SPECIAL-PURPOSE ROOMS						
Easy cleaning	● ● PUR	● ● PUR	•	•		
Castor chair suitability	••	••	•	•		
If necessary conductivity	● ● LCH	● ● Conductive		•		
Resistance to chemicals	● ● PUR	● ● PUR	•			
DINING ROOMS						•
Aesthetics, atmosphere	● Inlays	● Inlays	••			
Slip resistance R 9	••	••	••			Ė
Durability	••	••	••			
Easy cleaning	● ● PUR	● ● PUR	● ● PUR			
GYMS, SPORTS HALLS						
Resilience	Acoustic Linodur				••	
Slip resistance R 10 or Barefoot Class A	Linodur					Ţ
Durability	Linodur				••	
Force disassembly					••	
Treading warmth	•				•	
Easy cleaning	•				•	

[●] Recommended ● ● Highly recommended

^{*}Special verification or certificate for this segment additionally to the common technical product features.





CORRIDORS, STAIRS					
Slip resistance R 9	••	••	•		F
Durability	••	••	•	••	
Impact sound absorption	● ● Acoustic	● ● Acoustic		••	•)))
Easy cleaning	● ● PUR	● ● PUR	● ● PUR	•	
STORAGE ROOMS					
Durability	● ● Linodur	● ● Homogeneous	•	•	
Slip resistance R 9	••	•	•		Ţ`
Easy cleaning	● ● PUR	● ● PUR	● ● PUR	•	
Indentation resistance	● ● Linodur	● ● Homogeneous	•	•	ß
MEETING ROOMS					
Impact sound absorption	Acoustic	• Acoustic		••	->)))
Aesthetics, atmosphere	•	•	••	•	
Indentation resistance	••	••	•	••	
Castor chair suitability	••	••	•	••	
Durability	••	••	•	••	
ENTRANCE AREA					
Aesthetics, atmosphere	•	•	••	•	
Durability	••	••	••	•	
Easy cleaning	● ● PUR	● ● PUR	● ● PUR	•	
IT ROOMS					
Conductivity	● ● LCH	● ● Conductive		• Conductive	Ź
Castor chair suitability	● ● LCH	● ● Conductive		● ● Conductive	
Impact sound absorption				● ● Conductive	o)))



RECOMMENDATION FOR RETAIL



ENTRANCE AREA					
ENTRANCE AREA					
Aesthetics, atmosphere	•	•	••		
Durability	••	••	••		
Easy cleaning	● ● PUR	● ● PUR	● ● PUR		
Slip resistance R 9	••	••	••		F
SALES AREA					
Aesthetics, atmosphere	•	•	••	•	
Representation			••		
Durability	••	••	••	••	
Impact sound absorption	● ● Acoustic	● ● Acoustic		••	
Slip resistance R 9	••	••	••		F
Slip resistance R 10		● ● Favorite	••		F
Easy cleaning	● ● PUR	● ● PUR	••	••	
BREAK AREA					
Aesthetics	•	•	••	•	
Easy cleaning	● ● PUR	● ● PUR	● ● PUR	•	
OFFICES					
Castor chair suitability	••	••	•	••	
Impact sound absorption	● ● Acoustic	● ● Acoustic		••)))
Durability	••	••	•	••	
Easy cleaning	● ● PUR	● ● PUR	● ● PUR	••	

[●] Recommended ● ● Highly recommended

 $^{^{*}}$ Special verification or certificate for this segment additionally to the common technical product features.





CORRIDORS, STAIRS					
Durability	••	••	•	••	
Impact sound absorption	● ● Acoustic	● ● Acoustic		••)))
CAFÉ					
Aesthetics, atmosphere	• Inlays	• Inlays	••		
Slip resistance R 9	••	••	••		
Slip resistance R 10			••		F
Durability	••	••	••		S
Easy cleaning	● ● PUR	● ● PUR	● ● PUR		
STORAGE ROOMS					
Durability	● ● Linodur	● ● Homogeneous	•	•	
Slip resistance R 9	••	● ● Homogeneous	•		F
Slip resistance R 10			••		F
Indentation resistance	● ● Linodur	● ● Homogeneous	•	•	i



RECOMMENDATION FOR OFFICE



ENTRANCE AREA					
Aesthetics, atmosphere	•	•	••	•	
Smart, stylish design	•	•	••	•	
Corporate identity	● ● Logo Inlays	Eogo Inlays	• Logo Inlays	Logo Inlays	
Durability	••	••	••	•	
Slip resistance R 9	••	••	••		<u>F</u>
Sound insulation				••)))
MEETING ROOMS					
Comfort	Acoustic	• Acoustic	•	••	
Aesthetics	● Inlays	• Inlays	••		
Corporate identity	● ● Logo Inlays	• Logo Inlays	•		
Impact sound absorption	Acoustic	• Acoustic		••	•)))
Suitability for naturally ventilated floor				••	\$?
OFFICES					
Castor chair suitability	••	••	•	••	
Durability	••	••	•	••	
Suitability for naturally ventilated floor				••	\$2
Impact sound absorption	● ● Acoustic	● ● Acoustic		••)))

[●] Recommended ● ● Highly recommended

^{*} Special verification or certificate for this segment additionally to the common technical product features.





CORRIDORS, STAIRS					
Slip resistance R 9	••	••	•	•	Ę'
Easy cleaning	● ● PUR	● ● PUR	● ● PUR	•	
Durability	••	••	•	••	
Impact sound absorption	● ● Acoustic	● ● Acoustic		••)))
Suitability for naturally ventilated floor				••	\${
IT ROOMS					
Conductivity	● ● LCH	● ● Conductive		Conductive	Ź
Durability	● ● LCH	● ● Conductive		● ● Conductive	
Castor chair suitability	● ● LCH	● ● Conductive		● ● Conductive	
Impact sound absorption				● ● Conductive)))
STORAGE ROOMS					
Durability	● ● Linodur	● ● Homogeneous,	•	•	
Slip resistance R 9	••	● ● Homogeneous,	•		<u></u>
Easy cleaning	● ● PUR	● ● PUR	● ● PUR	•	
RESTAURANT					
Aesthetics, comfort	● Inlays	● Inlays	••		
Durability	••	••	••		
Slip resistance R 9	••	••	••		於



RECOMMENDATION FOR SPORTS SEGMENT AREA AND REQUIREMENTS SPORTS HALLS

SPORTS HALLS					
Area-elastic system				••	
Sport floor covering				••	
GYMS					
Point-elastic system				••	
Floor covering	Marmorette Acoustic			•	
AEROBIC STUDIOS					
Point-elastic system				••	
Floor covering	Marmorette Acoustic			•	
EXERCISE ROOMS					
Area-elastic system				••	
Point-elastic system				••	
Sports floor covering				••	
REHABILITATION CENTRES					
Point-elastic system				• •	
Floor covering	Marmorette Acoustic			•	
STORAGE ROOMS					
Durability	Linodur	Homogeneous		••	
CHANGING ROOMS					
Wet barefoot area Class A	● ● Linodur				彭

Recommended
 ● Highly recommended

^{*} Special verification or certificate for this segment additionally to the common technical product features.





CORRIDORS, STAIRS						
Durability	••	••	••	•	•	
OFFICES						
Castor chair suitability	••	•	•	••	•	
Durability	••	•	•	••	•	
ENTRANCE AREA						
Aesthetics, atmosphere	••	•	••		•	
Durability	••	••	•		•	
Easy cleaning	● ● PUR	● ● PUR	● ● PUR			
RESTAURANT						
Aesthetics, comfort	● ● Inlays	● Inlays	••			
Durability	••	••	••			
Slip resistance R 9	••	••	••			F

ARMSTRONG ACCESSORIES



Key, the full story technically speaking



Classification EN 685 class 23 domestic heavy



Classification EN 685 class 31 commercial moderate



Classification EN 685 class 32 commercial general



Classification EN 685 class 33 commercial heavy



Classification EN 685 class 34 commercial very heavy



Classification EN 685 class 41 industrial moderate



Classification EN 685 class 42 industrial general



Classification EN 685 class 43 industrial heavy



PUR Eco System (High-quality surface reinforcement)



LPX Finish (Standard surface for linoleum)



Building Research Establishment certificate



Certificate international Basketball federation



Certificate German Volleyball federation



RAL: suitable for gym floors (area elastic flooring)



Brand name of fibre for fibrebonded carpets



RAL classification highly robust for fibrebonded carpets



Armstrong Floor Protect (Anti soil and stain treatment)



EN 425 EN 985 Suitable for castor chair continuous use



EN 985 Suitable for castor chair, occasional use (Domestic)



EN 1815 Antistatic



EN 1081 ISO 10965 Conductivity (<10⁹ Ohm / <10⁶ Ohm)



EN 12524 Suitable for underfloor heating



EN 1963 Stairs continuous use



EN 12825 Suitable for raised floors



EN 1399 Cigarette resistance

EN 423

EN 13553



Resistance to chemicals



EN 423 Staining resistance

Water tightness



EN 13501-1 Reaction to fire (class $B_{\rm fl}$ -s1 / $C_{\rm fl}$ -s1 / $E_{\rm fl}$)

Luxury Classification



EN 13893 Slip resistance (dry condition)

EN 1470



EN 13893 Slip resistance (enhanced slip)



Tiles / planks



Broadloom / sheet



Wall covering



Fire certificate for ships



German environmental certificate "Blauer Engel"



Scandinavian environmental certificate "Swan"-label



Environmental certificate for linoleum in Europe



Austrian environmental certificate for linoleum



Environmental certificate for carpets in Europe



Applied harmonized standards



17 dB



17 dB



14 dB



ISO 9001 Certified company for Quality Management System ISO 9001



ISO 14001 Certified company for Environmental Management System ISO 14001



Certified company for Quality Management System ISO 9001



ISO 14001 SGS



Certified company for Quality Management System

Armstrong







